

Stationary Compactors



TP-5000HD

Tram-Pak Stationary Compactor

Designed For

- * Retailers * Hospitals * Hotels * Distribution Centers *
- * Manufacturing Centers * Recycling Centers * Home Centers *

When the TP-5000HD Series was designed, we challenged our engineers to see how long the machines could hold up in the field. We are pleased to say those machines originally built in the early 70's are still performing. All components are built using heavy-duty structural steel components and welded by AWS certified technicians. This unit has standard 3 button controls (On/Off key switch, mushroom stop, auto reverse) and a 13' Sealite.

Specifications

Charge Box Capacity	5 Cu Yd
Clear Top Opening (L x W)	97" x 60"
Capacity Per Hour	47 cy/hr

Performance Characteristics

Cycle Time	76 sec
Total Normal Force	84,666 lbs
Total Maximum Force	100,060 lbs
Normal Ram Face Pressure	41.7 psi
Maximum Ram Face Pressure	49.3 psi

Electrical Equipment

Electrical Motor 208 / 230 / 460	3 Phase
Electrical Control Voltage	120 VAC

Hydraulic Equipment

Hydraulic Pump Capacity	15 gpm
Normal Pressure	2200 psi
Maximum Pressure	2600 psi
Hydraulic Cylinder	7" Bore
Hydraulic Cylinder	4" Rod
Weight	lbs